

ERW CASING CONFORMING TO API 5CT

DIMENSIONS, WEIGHTS AND END FINISH

Outside Diameter		Normal Weight T&C		Normal Weight Plain-end		Wall Thickness		TYPE OF FINISH GRADE		COUPLING OD	THREAD TYPES TPI	
In.	mm	lb/ft.	Kg/mtr	lb/ft.	Kg/mtr	Inch	mm	H-40	J-55 K-55	mm	STC LTC	BTC
6 5/8	168.28	20.00	29.76	19.51	29.06	0.288	7.32	PS	PSLB	187.71	8	5
6 5/8	168.28	24.00	35.72	23.60	35.13	0.352	8.94	-	PSLB	187.71	8	5
7	177.80	20.00	29.76	19.56	29.12	0.272	6.91	PS	PS	200.03	8	-
7	177.80	23.00	34.23	22.65	33.70	0.317	8.05	-	PSLB	200.03	8	5
7	177.80	26.00	38.69	25.69	38.21	0.362	9.19	-	PSLB	200.03	8	5
8 5/8	219.08	24.00	35.72	23.60	35.14	0.264	6.71	-	PS	244.48	8	-
8 5/8	219.08	28.00	41.67	27.04	40.24	0.304	7.72	PS	-	244.48	8	-
8 5/8	219.08	32.00	47.62	31.13	46.33	0.352	8.94	PS	PSLB	244.48	8	5
8 5/8	219.08	36.00	53.57	35.17	52.35	0.400	10.16	-	PSLB	244.48	8	5
9 5/8	244.48	32.30	48.07	31.06	46.20	0.312	7.92	PS	-	269.88	8	-
9 5/8	244.48	36.00	53.57	34.89	51.93	0.352	8.94	PS	PSLB	269.88	8	5
9 5/8	244.48	40.00	59.53	38.97	57.99	0.395	10.03	-	PSLB	269.88	8	5
10 3/4	273.05	32.75	48.74	31.23	46.50	0.279	7.09	PS	-	298.45	8	-
10 3/4	273.05	40.50	60.27	38.91	57.91	0.350	8.89	PS	PSB	298.45	8	5
10 3/4	273.05	45.50	67.71	44.26	65.87	0.400	10.16	-	PSB	298.45	8	5
10 3/4	273.05	51.00	75.90	49.55	73.75	0.450	11.43	-	PSB	298.45	8	5
13 3/8	339.72	48.00	71.43	46.02	68.48	0.330	8.38	PS	-	365.12	8	-
13 3/8	339.72	54.50	81.10	52.79	78.55	0.380	9.65	-	PSB	365.12	8	5
13 3/8	339.72	61.00	90.78	59.50	88.55	0.430	10.92	-	PSB	365.12	8	5
13 3/8	339.72	68.00	101.19	66.17	98.46	0.480	12.19	-	PSB	365.12	8	5